
KAWASAKI STEEL TECHNICAL REPORT


No.38 (April 1998) Ironmaking Technology and Tubular Products Technology

Technical Consideration of the Niigata-Sendai Natural Gas Pipeline

Osamu Tsujimura, Hideaki Sugai, Hidehiko Koizumi


Technical Consideration of the Niigata-Sendai Natural Gas Pipeline^{*}






_	1 <u>2277</u>
- 	
i	

Table 5 Result of mechanical tests





2 / = = =	
9	
,	
	€ 1-
· .	
° λ	
йн х 	
\	
· · · · · · · · · · · · · · · · · · ·	
че че на	
ř.	
<u></u>	
стана -	
·	
-	
7	
۱	

	stock and delivery control subsystem, a quality cor	400	<u></u>]	
` `				
J				
•F •••				
n				
<u></u>				
و <u>ا</u> لم				
1				
·				
<u>ب</u>				
<u> </u>				
	}			
	۱ ۲			
) 			
	·			
	·			
	·			

15		used. The transport capacity was found by a steady-flow analysis using the pipe roughness determined in the above simulation and the start pressure at Niigata and
2		
	t,	
	,	
) #		
<u> </u>		
جو ج		
·		
•		
·		
1 T P-		
	ш. <u>.</u>	
· · · · · · · · · · · · · · · · · · ·		
	·	
·		
,		
4		
·		
· · ·		
a de la companya de la		
Y		